

OIL223M



K.AC.003



TECHNICAL FEATURES:

- Head made of metal with 3 single phase brush motors double stage by-pass
- Independent switches for each motor
- Centrifugal pump, single phase, with open rotor to discharge the liquid, power 0.9 kW, delivered quantity of 200 l/min. with water
- Electric cable 10m long with CEE 2P+T plug
- Cartridge filter oil proof for oil mists Ø276x210mm
- Quick inlet Ø50mm
- Container for liquids with 220l capacity
- Container for shaving with 60l capacity
- Rear wheels of cast iron Ø150mm, front wheels Ø150mm with brake
- Full painted version in Ral 7001 (grey)
- Available in three phase version
- Discharge hose Ø30 (4 m. long) with manual ball valve to discharge the sucked liquids
- Included in the supply accessories Ø50mm, K.AC.003:
 - 3mt oilproof flex hose Ø50 cod. 35.02.09.050
 - n.1 bent connection Ø50 cod. 65059
 - n.1 rubber cone oilproof Ø50 cod. 65053
 - n.1 oilproof conic nozzle Ø50 cod. 65072
 - n.1 hose connector Ø50 cod. 65044
 - n.2 hose clamp Ø50 cod. 30014

		OIL223M
Tension/ Voltage	Volts	1x 120V/60Hz
Power	Watt	4650 (3300+900)
Depression max	mbar	200
Max air flow	m ³ /h	510
Primary filter surface	m ²	-
Liquid expulsion pump flow rate (with water)	lt/m	200
Container capacity for liquids	Lt	220
Container capacity for chips	Lt	60
Product inlet	mm	Ø50
Noise level	DbA	77
Overall dimensions	Cm	60X145X190H
Weight	Kg	130
Protection	IP	43